

6700GLX

The **Clamco 6700GLX** automatic L-bar sealer has the advantages you need—an enhanced microprocessor PLC, touch screen interface and I/O diagnostics, memory for up to 20 package sizes, interface tunnel controls, self-adjusting scrap take-up wheel, microperforators for uniform air evacuation— and much more. All resulting in an automatic L-bar sealer with outstanding speed, throughput and performance to maximize productivity and profits.

FEATURES & BENEFITS

- Solid frame construction
- Production speeds of up to 40 packages per minute
- Heavy-duty hot knife sealing system
- PLC controlled
- Touch screen operator interface
- Built-in self diagnostics
- Product memory for up to 20 package configurations
- Easy load film cradle with film splitter and static eliminator
- Adjustable jaw opening for products up to 8" high
- Product alignment guides
- Horizontal and vertical product sensors
- Variable conveyor speed up to 100 fpm
- Self-adjusting scrap take-up reel
- Micro-Perf perforators for uniform air evacuation
- Motorized film unwind
- Casters and levelers



User friendly touch screen



Variable speed conveyor



Safety cover

OPTIONS & ACCESSORIES

- Various seal knife options available
- Tunnel controls integrated through PLC and interface
- Closing conveyor
- Printed film registration
- Split conveyor for product staging
- Light package take-away
- In-feed product sensor
- Film economizer
- Tail eliminator
- Hole punch
- FDA in-feed belt

SPECIFICATIONS

Speed	up to 40 packages/min
Maximum Film Width	23"
Maximum Product Height	8"
Hot Knife Sealing System	18" x 23" seal area
Machine Dimensions	69" Lx 50" Wx 51"H
Machine Weight	370 lbs (168 kg)
Electrical Requirements	120V, 15A, 2,100 w
Air Requirements	80 psi, 5 cfm

CLAMCO
A PAC Machinery Company