Ranpak Void Fill Systems...

the Natural Choice



FillPak TT Cut Mechanism

makes packing with paper even easier

Gives FillPak TT the Ability to Cut and Pre-define Paper Lengths

FillPak TT with cut mechanism converts fanfold kraft paper into a PaperStar™ configuration for fast and efficient void filling.

In addition to adding a cut mechanism to the FillPak TT, the upgrade also gives the operator the ability to pre-set paper lengths via an Electronic Delivery System (EDS) mode. The unit can be set up to dispense void fill material in lengths of 12 inches up to 10 feet.

The TT with cut mechanism has the same small footprint as the regular FillPak TT and can be easily adapted to any packing environment or integrated into areas with limited space.

Fast - output of 70 inches of paper per second

Versatile - allows users to program pre-set lengths of paper

Compact- small, lightweight and easy to use for facilities with multiple packing stations

Adaptable - converter height and head angles are adjustable for ease and comfort while loading or packing

Environmentally Friendly - 100% biodegradable, recyclable and renewable paper





Specifications



Converter Head (approximate measurements)*

Width	17"	
Length	24"	
Depth	14"	
Weight	27 lbs.	
Power	100/115 VAC, 1 phase	
Feed Rate	70 inches/second	
Cut Method	Electric Motor	
Operating Modes	Footswitch	

Stand (approximate measurements)*

	Table Stand	Floor Stand
Min./Max. Height**	49" - 59"	74" - 84"
Weight***	54 lbs.	66 lbs.

^{*}Size specifications do not include accessories.

Paper Bundle

Paper Type	Width (inches)	Basis Weight (lbs.)	Length (feet)	Weight (lbs.)
Fanfold Box	15	30*	1,660	22
Fanfold Box	15	45	1,200	24

^{*30-}lb. also available in 100% recycled and white

Paper Pallet

Bundle Type	Bundles per Pallet	Dimensions (inches)	Weight (lbs.)
30 lb.	65	48 x 40 Depth	1,500
45 lb.	65	48 x 40 Depth	1,517

Accessories



Wind Guard Kit -Universal



Battery Conversion Kit



Dual Footswitch Kit



Kneeswitch

Systems Engineering

Ranpak can increase your output and productivity by integrating our converters into your packaging lines. Our System Engineers can also design a custom solution to fit your unique situation and application for the most efficient, safe and user-friendly operation.

^{**}Min./Max. height dimensions are measured with the head at its maximum tilt.

^{***}Includes the weight of the head.