

MTLW Series Comparison Chart



Model	Machine Dimensions Length × Width × Height	Carton Range* Length (min max.) x Width (min max.) x Height (min max.)	Conveyor Height Adjustment Height (min max.)	Cartons per min.	Shipping Weight (lbs.)
MTLW22-2 2" Tape Head	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2"** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW22-3 3" Tape Head	(46.1") x (33.5") x (55.5")	(6.0" - U) x (8.2"** - 19.7") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	388
MTLW32-2 2" Tape Head	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2"** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	416
MTLW32-3 3" Tape Head	(46.1") x (43.0") x (55.5")	(6.0" - U) x (8.2"** - 30.0") x (0.5" - 20.3")	(20.5" - 30")	Up to 40	416

Information subject to change without notice.

U - Unlimited All Models available in High Speed & Stainless Steel * Outside Dimensions Only ** With narrow side rail adapter

www.bestpack.com Version 2.2_0118