

AT4E L-Feed Stainless

Fully Automatic 4-Edge Carton Sealer with L-turn

The BestPack AT4E Stainless Steel Series is an operator free, four outer edge carton sealer with corner seals, using pressure sensitive tape. These carton sealers are designed to eliminate costly hand taping of the four outer edges where pilfer proofing and protection of your product from outside environment is necessary. The AT4E Stainless Steel model is designed for uniform edge sealing applications where there is a wet environment. The units are designed with an automatic front side feed 90 degree box turn.

All BestPack stainless steel sealers are made with food grade 304 stainless steel for 21 CFR 110 compliance and include 304 High Speed stainless steel tape heads. Units are available for either splash resistant or wash-down applications. This unit is also available in standard finish. Standard 3" Tape Head.



Key Points of the Carton Sealer



Features

- Heavy Duty 3mm Welded 304 Food Grade Stainless Steel Frame Including Upper Welded Legs
- Seals All Four Outside Carton Edges Including All Corners
- 90 Degree Carton Turn Using Front Side Carton Infeed
- Top and Bottom Four Belt Drive System with 1-piece Molded Belts and V-belt Guide
- Top and Bottom Four 3" Pop-Out BestPack High Speed 304 Stainless Steel Tape Heads
- Low Tape/No Tape On Carton/No Cut Sensors with Malfunction Alarm and Three Color Light
- Motor Drive Uniform Height Adjustment
- Heavy Duty Upper Assembly Four Post System
- Heavy Duty SMC Oil-less Cushioned Air-cylinder

- Aluminum Framed Interlock Safety Gates Where Needed
- Tape Roll Length: 1,000 yd.
- Quality UL Approved Electrical Parts

Options

- Spare Parts Kit
- Available in Either a Left Side Infeed or a Right Side Infeed (Side Infeed Turns Carton 90 Degrees for Edge Seal Carton Position)

CUSTOMIZATION

- 304 Stainless MSD or 304 Stainless AS-S
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer

www.bestpack.com

QUA

Version 2.6_0218

OVAT

Extra Accessories to Improve Efficiency



Spare Parts Kit





High Speed Motor Upgrade (Up to 100 ft. per min.)



304 Stainless Steel Manual Sidedrive



304 Stainless Steel Spare Tape Head

Machine & Carton Specifications

110 Volts 60 Hz Power Requirements		Up to 8 Cartons/min. Speed		80 PSI 10 SCFM Air Requirements		1	1,550 - 1,970 lbs Shipping Weight		
Model	Machine Dimensions Length × Width × Height		Carton Range Length (min max.) x Width (min max.) x Height (min max.)		Conveyor Height Adjustment Height (min max.)		Cartons per min.	Shipping Weight (lbs.)	
AT4EL22-3S 3" Tape Head	(78.9") x (48.	5") x (63.0")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")		Determined at the time of order		Up to 8	1,550	
Also Available in Straight Feed									
AT4ES22-3S 3" Tape Head	(110.3") x (49	.8") x (60.5")	(10.3" - 23.5") x (9.8" - 23.5") x (9.8" - 23.5")	Determined at the time of c	order	Up to 8	1,970	

Information subject to change without notice.

