

# **MS Bottom Only**

#### **Bottom Only Carton Sealer**

The BestPack MS20 Series Bottom Sealer Tape Carton Sealer is our most popular. The unit is an operator-fed adjustable carton sealing machine designed to cater to the needs of light-to-heavy duty uniform bottom carton closure applications.

Our MS20 line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



#### **Key Points of the Carton Sealer**



- Two Side Belt Drive
- Adjustable Bed Height 20.5" to 30.0"
- · Width Adjustment Either Side of Carton Sealer
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame
- UL Approved Electrical Parts
- High Speed Tape Head
- Designed for uniform applications Capable of Interchanging 2" or 3"
- · Electrical On/Off Box can be Mounted on Either Side of Carton Sealer

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft. per min.)
- Interlock Safety Gates
- Food Grade 304 Stainless Steel

C

- Locking Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer

www.bestpack.com


Version 2.5 0218

ISTOMIZATION

All contents are Copyright © 2018 BestPack Packaging Systems. All rights reserved. This document is BestPack Public Information.

Ονατ

## **Extra Accessories to Improve Efficiency**



Spare Parts Kit

- Interlock Safety Gates
- High Speed Motor Upgrade
- Carton Sealing Tape



Locking Casters



Long Infeed/Exit Conveyor w/ L-Bracket



Spare Tape Head

### **Machine & Carton Specifications**

<b>110 Volts 60 Hz</b> Power Requirements		<b>Up to 40 Cartons/min.</b> Speed		<b>None</b> Air Requirements			<b>263 - 310 lbs</b> Shipping Weight		
Model	Machine Dimensions Length × Width × Height		Carton Range* Length (min max.) × Width (min max.)		Conveyor Height Adjust Height (min max.)	nent	Cartons per min.**	Shipping Weight (lbs.)	
MS20-2 2" Tape Head	(39.5") × (28.3") × (29.4")		(6.0" - U) x (4.25" - 20.0")		(20.5" - 30.0")		Up to 40	263	
MS20-3 3" Tape Head	(39.5") x (28.	3") x (29.4")	(6.0" - U) x (5.25" - 20.0")		(20.5" - 30.0")		Up to 40	263	
MS30-2 2" Tape Head	(39.5") x (39.4") x (29.4")		(6.0" - U) x (4.25" - 30.0")		(20.5" - 30.0")		Up to 40	310	
MS30-3 3" Tape Head	(39.5") × (39.4") × (29.4")		(6.0" - U) x (5.25" - 30.0")		(20.5" - 30.0")		Up to 40	310	

Information subject to change without notice.

U - Unlimited

\*Outside Dimensions Only

\*\*Based on 12" Long Carton

All Models available in High Speed & Food Grade 304 Stainless Steel

