

## MSAG Series

### Manual Sidedrive for Agriculture Products

The BestPack MSAG is a Semi-Automatic Uniform Tape Carton Sealer. The MSAG is designed for unique applications where the sealer needs to place two strips of tape on the top of the carton, even out to the top edges of the carton. Yet still seal in the center of the carton on the bottom. The upper assembly and bottom assembly can accept center seal with 2", 3" and 6" tape heads, or double sealing the top of the carton that can be accomplished with either 2" tape heads or 3" tape heads. A top 3-flap folder and front extended side belts are included.

Our MSAG incorporates our exclusive 2", 3", and 6" High Speed pop-out pressure-sensitive tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



## Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



2 Top & 1 Bottom Seal

## Features

- Semi-Automatic Uniform Carton Sealer
- Extended Side Belt Drives
- Top 3-Flap Folder
- Adjustable Acme Screw Drive Upper Assembly that Allows for Top Center Seal, or Splits Apart for Double Taping on Top Even Out to the Outside Edges of the Carton
- Upper Assembly Accepts 2", 3", and 6" High Speed Tape Heads for Top Center Seal. It Also Accepts 2" and 3" Tape Heads for Double Top Seal.
- Bottom Center Seals with either 2", 3" or 6" High Speed Tape Heads
- Tape Roll Lengths: 1,000 yd. and 1,500 yd. (1,000 yd. only for 6")
- Heavy Duty 8 Roller Top Compression Unit

- Width/Height Adjustment Either Side of the Carton Sealer
- Extra 4" Carton Height Adjustment Available on Upper Assembly
- High Speed Motors
- Adjustable Bed Height from 20.5" to 30.0"
- Electrical On/Off Box can be Mounted on Either Side of the Carton Sealer
- Heavy Duty Frame
- UL Approved Electrical Parts

## Options

- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Heavy Duty Locking Casters
- Right Justified

# Extra Accessories to Improve Efficiency



Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor  
w/ L-Bracket



Spare Tape Head

- Short Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

## Machine & Carton Specifications

**110 Volts 60 Hz**  
Power Requirements

**Up to 35 Cartons/min.**  
Speed

**None**  
Air Requirements

**575 lbs**  
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.***	Shipping Weight (lbs.)
MSAG-3HEB** <b>3" Tape Head</b>	(58.5") x (43.3") x (65.0")	(6.0" - U) x (8.5" - 31.0") x (6.25" - 20.25")	(20.5" - 30.0")	Up to 35	575

Information subject to change without notice.

U - Unlimited  
\* Outside Dimensions Only  
\*\* High Speed  
\*\*\* Based on a 12" long carton