

MTSS

Manual Side Sealing Carton Sealer

The BestPack™ MTSS Series is an operator-fed, adjustable carton sealer designed to effectively seal cartons that need to be filled from the side as a result of the product's weight, shape, and size.

Our MTSS line incorporates our exclusive 2" or 3" pop-out pressure-sensitive "High Speed" tape heads with BestPack's patented tab adjustment. All BestPack units are available in our standard baked enamel finish and food grade 304 stainless steel for 21 CFR 110 compliance.



Key Points of the Carton Sealer



Operator Fed



Uniform Cartons



Side Seal

Features

- Each Side Tape Head is Individually Adjustable. The Individual Adjustability Allows Complete Control Over the Location Where the Tape can be Applied on the Side of the Carton. This Allows for the Taping of Side RSC and FOL Cartons.
- 4 Belt Drive - 2 Top and 2 Bottom Belts
- Adjustable Bed Height 20.5" - 30.0"
- The MTSS Series are Designed with Four Adjustable Legs for Quick, Easy Height Adjustment to Production Lines.
- Tape Roll Lengths: 1,000 yd., 1,500 yd., 2,000 yd.
- Heavy Duty Frame

- UL Approved Electrical Parts
- Capable of Interchanging 2" or 3" Tape Heads
- Electrical On/Off Box can be Mounted on Either Side of the Sealer

Options

- Spare Parts Kit
- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Stainless Steel
- Locking Casters
- Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Low or No Tape Sensor

Extra Accessories to Improve Efficiency



Spare Parts Kit May Vary

Spare Parts Kit



Locking Casters



Long Infeed/Exit Conveyor
w/ L-Bracket Stabilizer



Spare Tape Head

- High Speed Motor Upgrade (Up to 125 ft./mm.)
- Short Infeed/Exit Conveyor w/ L-Bracket Stabilizer
- Food Grade 304 Stainless Steel
- Carton Sealing Tape

Machine & Carton Specifications

110 Volts 60 Hz
Power Requirements

Up to 40 Cartons/min.
Speed

N/A
Air Requirements

548-688 lbs
Shipping Weight

Model	Machine Dimensions Length x Width x Height	Carton Range* Length (min. - max.) x Width (min. - max.) x Height (min. - max.)	Conveyor Height Adjustment Height (min. - max.)	Cartons per min.	Shipping Weight (lbs.)
MTSS22-2/3 2" or 3" Tape Head	(45.5") x (33.6") x (53.0")	(6.0" - U) x (7.5" - 21.0") x (4.5" - 19.5")	(20.5" - 30")	Up to 40	548
MTSS33-2/3 2" or 3" Tape Head	(45.5") x (52.0") x (71.0")	(6.0" - U) x (14.3" - 31.0") x (8.5" - 30.0")	(20.5" - 30")	Up to 40	688

Information subject to change without notice.

U - Unlimited
* Outside Dimensions Only
All Models available in High Speed & Food Grade 304 Stainless Steel