

## e-SolarMark+ CO<sub>2</sub> Laser Coding System

Matthews Marking Systems' e-SolarMark+ CO<sub>2</sub> laser coder is ideal for high speed food, beverage, and pharmaceutical packaging applications, in addition to many different industrial applications. These lasers can permanently code onto cardboard, coated metals, glass, leather, paper, plastics, and wood. There are five power options to choose from, based on your speed and performance requirements.

The Matthews laser coding systems provide many interface options to connect to remote devices such as PLC's, packaging equipment, material handling equipment, and many other peripheral devices used in the manufacturing environment. Matthews' laser systems have the greatest optical hardware options, allowing the laser to be mounted in confined areas of a production line, and they are capable of running in static or dynamic mode. There are two control unit models (15" color touch screen interface or an OEM control unit without an interface) and Matthews provides free message design software with every laser system.

The eSolarMark+ includes upgraded PC software, enhanced diagnostic features, and a user-friendly, 15" graphic interface. Control unit allows full editing of messaging while the laser functions in print mode.

### Features:

- Software includes preview and editing window for ease of use
- Range of lens and scanning heads allows for a wide variety of focal lengths and marking areas
- Vector quality, permanent coding of text, date and time codes, serial numbers, barcodes and 2D codes, and graphics
- Clean and eco-friendly coding system
- Improve overall equipment effectiveness (O.E.E.)



## e-SolarMark+

		10.6µm Wavelength				9.3µm Wavelength		10.2µm Wavelength					
LASER OUTPUT POWER		10W	30W	55W	20W	45W	30W						
ELECTRICAL REQUIREMENTS	115V 60Hz/230V 50Hz, Single Phase												
POWER CONSUMPTION		400W	650W	1100W	650W	1100W	650W						
COOLING	Air cooled at ambient temperature 41-104° F (5-40° C) Up to 100% of laser duty cycle	Air cooled at ambient temperature 41-104° F (5-40° C) or Water cooled (HD e-SolarMark models only) at ambient temperature 104-113° F (40-45° C) or in dirty, dusty, humid environment. Up to 100% of laser duty cycle											
OPERATING ENVIRONMENT	Ambient temperature 41-104° F (5-40° C) Humidity up to 80% non-condensing												
ENCLOSURE TYPE	IP52, NEMA 12 / IP65, NEMA 4 (Optional)												
DIMENSIONS AND WEIGHT	Control Unit	L: 12.5" W: 15.6" H: 7" 18 lb	L: 318 mm W: 395 mm H: 178 mm 8 kg	L: 12.5" W: 15.6" H: 7" 18 lb	L: 318 mm W: 395 mm H: 178 mm 8 kg	L: 15.4" W: 18.3" H: 7" 18 lb	L: 390 mm W: 464 mm H: 178 mm 8 kg	L: 12.5" W: 15.6" H: 7" 18 lb	L: 318 mm W: 395 mm H: 178 mm 8 kg	L: 15.4" W: 18.3" H: 7" 18 lb	L: 390 mm W: 464 mm H: 178 mm 8 kg	L: 12.5" W: 15.6" H: 7" 18 lb	L: 318 mm W: 395 mm H: 178 mm 8 kg
	Marking Unit (dimensions for standard marking unit with f18 scanning head and no modules)	L: 32.2" W: 5.5" H: 5.5" 29 lb	L: 818 mm W: 140 mm H: 140 mm 13 kg	L: 27.6" W: 5.5" H: 5.5" 29 lb	L: 700 mm W: 140 mm H: 140 mm 13 kg	L: 34.6" W: 5.9" H: 5.9" 40 lb	L: 878 mm W: 150 mm H: 150 mm 18 kg	L: 27.6" W: 5.5" H: 5.5" 29 lb	L: 700 mm W: 140 mm H: 140 mm 13 kg	L: 34.6" W: 5.9" H: 5.9" 40 lb	L: 878 mm W: 150 mm H: 150 mm 18 kg	L: 27.6" W: 5.5" H: 5.5" 29 lb	L: 700 mm W: 140 mm H: 140 mm 13 kg

MARKING SPECIFICATIONS					
Flat field (F-Theta) lens (up to 400 mm x 400 mm marking window)					
LENS TYPE	LF2	LF70	LF4	LF140	LF210
MARKING FIELD IN mm	50 x 50	70 x 70	100 x 100	140 x 140	210 x 210

LANGUAGES AVAILABLE		
English	Spanish	Swedish
Chinese	Italian	Portuguese
French	Dutch	
German	Polish	


COMMUNICATION
<ul style="list-style-type: none"> <li>– USB/RS232/Ethernet 10 Base T</li> <li>– Input/output connector for: system interlocks, remote start/stop, ready, marking, status signals, and remote key switch connection.</li> <li>– SolMark II job edition software available for Windows XP, Vista, 7, 8</li> </ul>

OPTIONS
<ul style="list-style-type: none"> <li>– Control unit, touchscreen and OEM base</li> <li>– Scanning head mounting extension modules</li> <li>– Product detector and shaft encoder</li> <li>– Fumes/dust extractor (with active carbon &amp; HEPA filter)</li> <li>– Umbilical lengths 3m, 4m, 6m, 10m</li> <li>– Red laser pointer for marking position preview</li> </ul>

**CE AND CDRH COMPLIANT**

# DANGER

**Invisible Laser Radiation**  
Avoid Eye or Skin Exposure to Direct or Scattered Radiation



**CO<sub>2</sub> Laser**

10,600nm, 150W Max Class IV Laser Product

